



ZC260

ZC260 Millimeter-Wave Converters

Part-No.: 3628.5682.02

Product Description

Key Features:

- variable output power
- wide dynamic range
- wide frequency range
- highly stable measurement
- convenient handling





Technical Specifications

Test Port

Frequency Range [GHz]	170 to 260
Port Type	WM-1092 (UG387/U flange compatible)
Output Power [dBm (typ.)]	170 to 240 GHz > -8 dBm, typ. -4 dBm 240 to 260 GHz > -12 dBm, typ. -7 dBm
Output Power Attenuation [dB]	0 to 40
Input Power Damage Level [dBm]	+20
Stability (Magnitude [dB] / Phase [°] (typ.))	typ. < 0.4 dB and typ. < 4°

Source Input (RF IN)

Frequency Range [GHz]	14.16 to 21.66
Port Type	2.92 mm, female
Input Power Range [dBm]	+5 to +10

Local Oscillator Input (LO IN)

Frequency Range [GHz]	14.16 to 21.66
Port Type	SMA, female
Input Power Range [dBm]	+5 to +10

Measurement Output (MEAS OUT)

Frequency Range [MHz]	5 to 2000
Port Type	SMA, female

Reference Output (REF OUT)

Frequency Range [MHz]	5 to 2000
Port Type	SMA, female

System Characteristics

Source match (without system error correction)	> 20 dB (n.trc.) ¹
Directivity (without system error correction)	> 20 dB (n.trc.) ¹
Dynamic Range [dB]	> 100, typ. 110

Dynamic range is defined as the difference between the data trace of the transmission magnitude with maximum test port output power and both test ports through-connected on the one hand and the RMS value of the data trace of the transmission magnitude produced by noise and crosstalk with test ports short-circuited on the other. The specification is valid without system error correction and at 10Hz measurement bandwidth. The dynamic range can be increased by using a measurement bandwidth of 1Hz.

¹ Without consideration of measurement uncertainty.



Typical Performance

